Material Safety Data Sheet



Advantage 15W40 CI-4, CH-4; 15W40 CI-4, CH-4, EO-M 10 TBN; 15W40 CH-4, EO-M 14 TBN; 15W40 Premium CI-

4+; 20W50 CH-4; HD 10W-30, CJ-4; HD 10W-30, CH-4, SJ; 15W40 CI-4, CI-4+ Mack

Premium Plus; 15W40 CI-4, CI-4 Plus, CH-4, EO-M 12 TBN Mack Premium Plus; 15W40 CJ-4 Mack PP '07; 15W40 Premium Plus CJ-4

1. Product and company identification

Product name : Advantage Multi-Grade Diesel Engine Oils: 15W40 Cl-4, CH-4; 15W40 Cl-4, CH-4, EO-M

10 TBN; 15W40 CH-4, EO-M 14 TBN; 15W40 Premium Cl-4+; 20W50 CH-4; HD 10W-30, CJ-4: 10W-30, CH-4. SJ: 15W40 Cl-4. Cl-4+ Mack Premium Plus: 15W40 Cl-4. Cl-4 Plus.

CH-4, EO-M 12 TBN Mack Premium Plus; 15W40 CJ-4 Mack PP '07; 15W40 Premium Plus CJ-4

Material uses : Heavy duty oil.

Supplier/Manufacturer : Advanced Lubrication Specialties

420 Imperial Court East Bensalem, PA 19020

Code : 502; 508; 512; 513; 514; 517; 519; 521; 523; 524; 528

Validation date : 05/01/2012

Responsible name : Atrion Regulatory Services, Inc.

In case of emergency : Transportation: 215-244-2114 8am-4:30pm EST Monday to Friday

CHEMTREC United States/Canada: 800-424-9300 24 hrs Everyday

2. Hazards identification

Physical state : Liquid.

Odor : Petroleum.

OSHA/HCS status : While this material is not considered hazardous by the OSHA Hazard Communication

Standard (29 CFR 1910.1200), this MSDS contains valuable information critical to the safe handling and proper use of the product. This MSDS should be retained and available

for employees and other users of this product.

Emergency overview : CAUTION!

MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION. PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION. HARMFUL OR

FATAL IF SWALLOWED. CAN ENTER LUNGS AND CAUSE DAMAGE.

Slightly irritating to the eyes, skin and respiratory system. Defatting to the skin. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not ingest. Avoid

breathing vapor or mist. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash

thoroughly after handling.

Routes of entry : Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Inhalation : Slightly irritating to the respiratory system.

Ingestion : Aspiration hazard if swallowed. Can enter lungs and cause damage.

Skin : Slightly irritating to the skin.

Eyes : Slightly irritating to the eyes.

Potential chronic health effects

Chronic effects : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or

dermatitis.

Carcinogenicity
 Mo known significant effects or critical hazards.
 Mutagenicity
 No known significant effects or critical hazards.
 Teratogenicity
 No known significant effects or critical hazards.
 Developmental effects
 No known significant effects or critical hazards.



Advantage Multi-Grade Diesel Engine Oils: 15W40 Cl-4, CH-4; 15W40 Cl-4, CH-4, EO-M 10 TBN; 15W40 CH-4, EO-M 14 TBN; 15W40 Premium Cl-4+; 20W50 CH-4; HD 10W-30, CJ-4; HD 10W-30 CH-4, SJ; 15W40 Cl-4, Cl-4+ Mack Premium Plus; 15W40 Cl-4, Cl-4 Plus, CH-4, EO-M 12 TBN Mack Premium Plus; 15W40 CJ-4 Mack PP '07; 15W40 Premium Plus CJ-4

2. Hazards identification

Fertility effects : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Ingestion : Adverse symptoms may include the following:

nausea or vomiting

Skin: Adverse symptoms may include the following:

irritation redness dryness cracking

Eyes : Adverse symptoms may include the following:

irritation watering redness

Medical conditions aggravated by overexposure : None known.

See toxicological information (section 11)

3. Composition/information on ingredients

United States

NameCAS number%Base Oils.See below.>76Zinc Alkyldithiophosphate68649-42-31 - 5

The Base Oil may contains one or more of the following ingredients: 61788-76-9, 64741-88-4, 64742-01-4, 64742-65-0, 64742-89-5, 64742-48-9, 64742-52-5, 64742-54-7, 64742-56-3

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

Eye contact: Check for and remove any contact lenses. In case of contact with eyes, rinse immediately with plenty of water. Get medical attention if symptoms occur.

Skin contact : Wash with soap and water. Get medical attention if symptoms occur.

Inhalation : If inhaled, remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms appear.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious person. Get

medical attention if symptoms appear.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.

Notes to physician : No specific treatment. Treat symptomatically. Contact poison treatment special

Notes to physician : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.



Advantage Multi-Grade Diesel Engine Oils: 15W40 CI-4, CH-4; 15W40 CI-4, CH-4, EO-M 10 TBN; 15W40 CH-4, EO-M 14 TBN; 15W40 Premium CI-4+; 20W50 CH-4; HD 10W-30, CJ-4; HD 10W-30 CH-4, SJ; 15W40 Cl-4, Cl-4+ Mack Premium Plus; 15W40 Cl-4, Cl-4 Plus, CH-4, EO-M 12 TBN Mack Premium Plus; 15W40 CJ-4 Mack PP '07; 15W40 Premium Plus CJ-4

Fire-fighting measures **5** .

Flammability of the product

Extinguishing media

: May be combustible at high temperature.

Suitable

: Use dry chemical, CO₂, water spray (fog) or foam.

Not suitable **Hazardous thermal** decomposition products : None known. : No specific data.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing

apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Accidental release measures

Personal precautions

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment (see section 8).

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Note: see section 1 for emergency contact information and section 13 for waste disposal.

Handling and storage

Handling

: Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.

Storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Exposure controls/personal protection 8.

United States

Product name Exposure limits

Base Oils. ACGIH TLV (United States). TWA: 5 mg/m³ 8 hour(s).

OSHA PEL 1989 (United States).

TWA: 5 mg/m3 8 hour(s).

Consult local authorities for acceptable exposure limits.

Date of issue : 05/01/2014 Page: 3/7 Powered by



Advantage Multi-Grade Diesel Engine Oils: 15W40 CI-4, CH-4; 15W40 CI-4, CH-4, EO-M 10 TBN; 15W40 CH-4, EO-M 14 TBN; 15W40 Premium CI-4+; 20W50 CH-4; HD 10W-30, CJ-4; HD 10W-30 CH-4, SJ; 15W40 CI-4, CI-4+ Mack Premium Plus; 15W40 CI-4, CI-4 Plus, CH-4, EO-M 12 TBN Mack Premium Plus; 15W40 CJ-4 Mack PP '07; 15W40 Premium Plus CJ-4

8. Exposure controls/personal protection

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Engineering measures

: No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Hygiene measures


: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection

Eyes : Safety glasses.
Skin : Lab coat.

Respiratory : A respirator is not needed under normal and intended conditions of product use.

Hands
Personal protective
equipment (Pictograms)



HMIS Code/Personal protective equipment

Environmental exposure

controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and chemical properties

: B

Physical state : Liquid.

Color : Amber. [Dark]
Odor : Petroleum.
Relative density : 0.87 @ 15.6°C

Vapor pressure : <0.13 kPa (<1 mm Hg)

Solubility : Insoluble in the following materials: cold water and hot water.

10 . Stability and reactivity

Stability

: The product is stable.

Hazardous polymerization

: Under normal conditions of storage and use, hazardous polymerization will not occur.

Conditions to avoid

Materials to avoid

: No specific data.

Hazardous decomposition

: Reactive or incompatible with the following materials: oxidizing materials.

products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.



Advantage Multi-Grade Diesel Engine Oils: 15W40 Cl-4, CH-4; 15W40 Cl-4, CH-4, EO-M 10 TBN; 15W40 CH-4, EO-M 14 TBN; 15W40 Premium Cl-4+; 20W50 CH-4; HD 10W-30, CJ-4; HD 10W-30 CH-4, SJ; 15W40 Cl-4, Cl-4+ Mack Premium Plus; 15W40 Cl-4, Cl-4 Plus, CH-4, EO-M 12 TBN Mack Premium Plus; 15W40 CJ-4 Mack PP '07; 15W40 Premium Plus CJ-4

11. Toxicological information

Acute toxicity

Inhalation : Slightly irritating to the respiratory system.

Ingestion : Aspiration hazard if swallowed. Can enter lungs and cause damage.

Skin : Slightly irritating to the skin.

Eyes : Slightly irritating to the eyes.

12. Ecological information

Environmental effects: No known significant effects or critical hazards.

13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

AERG : Not applicable.

Regulatory information

DOT/ IMDG/ IATA : Not regulated.

15. Regulatory information

United States

HCS Classification

U.S. Federal regulations

: Not regulated.

: TSCA 4(a) final test rules: Diphenylamine

TSCA 8(a) PAIR: Phenol, (tetrapropenyl) derivs.; Zinc Alkyldithiophosphate;

Diphenylamine

United States inventory (TSCA 8b): All components are listed or exempted.

TSCA 8(d) H and S data reporting: Zinc Alkyldithiophosphate: 2006

SARA 302/304/311/312 extremely hazardous substances: No products were found. **SARA 302/304 emergency planning and notification**: No products were found.

SARA 302/304/311/312 hazardous chemicals: No products were found.

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: No products were found.

Clean Water Act (CWA) 307: Zinc Alkyldithiophosphate

Clean Water Act (CWA) 311: No products were found.

Clean Air Act (CAA) 112 accidental release prevention: No products were found.

Clean Air Act (CAA) 112 regulated flammable substances: No products were found.

Clean Air Act (CAA) 112 regulated toxic substances: No products were found.



Advantage Multi-Grade Diesel Engine Oils: 15W40 Cl-4, CH-4; 15W40 Cl-4, CH-4, EO-M 10 TBN; 15W40 CH-4, EO-M 14 TBN; 15W40 Premium Cl-4+; 20W50 CH-4; HD 10W-30, CJ-4; HD 10W-30 CH-4, SJ; 15W40 Cl-4, Cl-4+ Mack Premium Plus; 15W40 Cl-4, Cl-4 Plus, CH-4, EO-M 12 TBN Mack Premium Plus; 15W40 CJ-4 Mack PP '07; 15W40 Premium Plus CJ-4

15. Regulatory information

State regulations

: Connecticut Carcinogen Reporting: None of the components are listed.

Connecticut Hazardous Material Survey: None of the components are listed.

Florida substances: None of the components are listed.

Illinois Chemical Safety Act: None of the components are listed.

Illinois Toxic Substances Disclosure to Employee Act: None of the components are listed.

Louisiana Reporting: None of the components are listed. Louisiana Spill: None of the components are listed. Massachusetts Spill: None of the components are listed.

Massachusetts Substances: The following components are listed: Base Oils.

Michigan Critical Material: None of the components are listed.

Minnesota Hazardous Substances: None of the components are listed.

New Jersey Hazardous Substances: The following components are listed: Zinc Alkyldithiophosphate

New Jersey Spill: None of the components are listed.

New Jersey Toxic Catastrophe Prevention Act: None of the components are listed. New York Acutely Hazardous Substances: None of the components are listed. New York Toxic Chemical Release Reporting: None of the components are listed. Pennsylvania RTK Hazardous Substances: The following components are listed: Zinc Alkyldithiophosphate

Rhode Island Hazardous Substances: None of the components are listed.

California Prop. 65
International regulations
International lists

: No products were found.

: This product, (and its ingredients) is (are) listed on national inventories, or is (are) exempted from being listed, in Australia (AICS), in Europe (EINECS/ELINCS), in Korea (TCCL), in Japan (METI), in the Philippines (RA6969).

16. Other information

Label requirements

: MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION. PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION. HARMFUL OR FATAL IF SWALLOWED. CAN ENTER LUNGS AND CAUSE DAMAGE.

Hazardous Material Information System (U.S.A.)

Health 2
Fire hazard 1
Physical Hazard 0
Personal protection B

HAZARD RATINGS

4- Extreme 3- Serious

2- Moderate 1- Slight

0- Minimal

See section 8 for more detailed information on personal protection.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)

Health 2 Flammability
Instability
Special

References: ANSI Z400.1, MSDS Standard, 2004. - Manufacturer's Material Safety Data Sheet. - 29CFR Part1910.1200 OSHA MSDS Requirements. - 49CFR Table List of Hazardous Materials, UN#, Proper Shipping Names, PG.



Advantage Multi-Grade Diesel Engine Oils: 15W40 CI-4, CH-4; 15W40 CI-4, CH-4, EO-M 10 TBN; 15W40 CH-4, EO-M 14 TBN; 15W40 Premium CI-4+; 20W50 CH-4; HD 10W-30, CJ-4; HD 10W-30 CH-4, SJ; 15W40 CI-4, CI-4+ Mack Premium Plus; 15W40 CI-4, CI-4 Plus, CH-4, EO-M 12 TBN Mack Premium Plus; 15W40 CJ-4 Mack PP '07; 15W40 Premium Plus CJ-4

16. Other information

Date of issue : 05/01/2014

Date of previous issue Version

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.