

SAFETY DATA SHEET

This safety data sheet complies with the requirements of: OSHA Hazard Communication Standard (29 CFR 1910.1200)

Product Name: Subaru Synthetic Motor Oil SAE 0W-20 GF-6, Revision Date: 08-Feb-2021

Keep Full

Product Code: 34070101-00000C010 Revision Number: 2

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE

COMPANY/UNDERTAKING

1.1 Product identifier

Product Name: Subaru Synthetic Motor Oil SAE 0W-20 GF-6, Keep Full

Other means of identification

Product Code: 34070101-00000C010

1.2 Recommended use of the chemical and restrictions on use

Recommended Use: Automotive Lubricant

1.3 Details of the supplier of the safety data sheet

Manufactured by: Idemitsu Lubricants America Corporation

701 Port Rd., Jeffersonville, IN. 47130

Telephone: 1-(812) 284-3300 Business hours: 8am-4:30pm est

Email: Ila.sds@idemitsu.com

24 Hour Emergency Phone Number: Within USA and Canada: 1 800-424-9300

Outside USA and Canada: + 1 703-741-5970

(collect calls accepted)

2. HAZARDS IDENTIFICATION

2.1 Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

2.2 Label elements

Not a dangerous substance or mixture according to the Globally Harmonized System (GHS).

Hazards not otherwise classified (HNOC)

Not applicable

2.3 Other information

Other hazards No information available

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable

3.2 Mixture

The product contains no substances which at their given concentration, are considered to be hazardous to health

Non-Hazardous Components

Chemical name	CAS-No	weight-%
Lubricating Base Stocks	Mixture	90-100

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

4. FIRST AID MEASURES

4.1 First Aid Measures

General Advice If symptoms persist, call a physician. Take a copy of the Safety Data Sheet when going for

medical treatment.

Skin Contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. If skin irritation persists, call a physician.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If eye irritation

Revision Date: 08-Feb-2021

persists: Get medical advice or attention.

Inhalation Move to fresh air in case of accidental inhalation of vapors. If breathing is difficult, give

oxygen. If not breathing, give artificial respiration. Call a physician immediately.

Ingestion Do not induce vomiting without medical advice. If vomiting occurs naturally, have casualty

lean forward to reduce the risk of aspiration. If symptoms persist, call a physician.

Protection of First-aidersUse personal protective equipment. Avoid contact with eyes, skin and clothing.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms See Section 11 for additional Toxicological information.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flammable Properties NFPA: Class IIIB Combustible Liquid

5.1 Suitable extinguishing media

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment

Unsuitable Extinguishing Media: Do not use a solid water stream as it may scatter and spread fire.

5.2 Specific Hazards Arising from the Chemical Keep product and empty container away from heat and sources

of ignition.

Hazardous combustion products

During a fire, smoke may contain the original material in addition

to combustion products of varying composition which may be toxic and / or irritating. Combustion products may include and

, .

are not limited to: Carbon oxides Nitrogen oxides (NOx) Sulphur oxides Metal Oxides Oxides of Phosphorus

5.3 Protective Equipment and Precautions for Firefighters:

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Revision Date: 08-Feb-2021

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists. Use personal

protection recommended in Section 8. Ensure adequate ventilation. Remove all sources of

ignition.

6.2. Environmental precautions

Environmental Precautions See section 12 for additional ecological information. Prevent further leakage or spillage if

safe to do so. Prevent product from entering drains. Do not allow into any sewer, on the ground or into any body of water. Do not flush into surface water or sanitary sewer system. Large Spills: Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into

waterways, sewers, basements or confined areas.

6.3 Methods and material for containment and cleaning up

Methods for Clean-up Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth,

diatomaceus earth, vermiculite) and place in container for disposal according to local /

national regulations (see section 13).

Spill Management

LARGE SPILLS Eliminate sources of ignition. Prevent additional discharge of material if possible to do so

without hazard. For small spills implement cleanup procedures; for large spills implement

cleanup procedures and, if in public area, keep public away and advise authorities.

WATER SPILLS Prevent liquid entering sewers, watercourses, or low areas. Contain spilled liquid with sand

or earth. Recover by pumping or with suitable absorbent. If liquid is too viscous for pumping, scrape up. Consult an expert on disposal of recovered material and ensure

conformity to local disposal regulations.

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Handling Do not breathe vapors, spray, or mist. Avoid contact with eyes,

skin and clothing. Use personal protection recommended in the SDS. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of

ignition.

Safe Handling Advice Handle in accordance with good industrial hygiene and safety

practices. Take precautionary measures against static

discharges.

7.2. Conditions for safe storage, including any incompatibilities

Storage Keep in properly labeled containers. Keep container tightly closed

in a dry and well-ventilated place.

Revision Date: 08-Feb-2021

Technical measures/Precautions Ensure adequate ventilation.

EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure Guidelines

Chemical name	OSHA PEL	ACGIH TLV	ACGIH OEL (STEL)	NIOSHT REL TWA	ILA IHG	ILA ROEG	ILA Internal Exposure Limit
Oil mist, mineral	TWA: 5 mg/m³	TWA: 5 mg/m³		TWA 5 mg/m ³ ST 10 mg/m ³			

8.2 Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal Protective Equipment

Safety glasses equipped with side shields are recommended as minimum protection in Eye/face protection

industrial settings.

Choose the appropriate protective clothing and gloves based on the tasks being performed Skin protection

to avoid exposed skin surfaces. Glove Type: Neoprene, Nitriles

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved Respiratory protection

> respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

Do not eat, drink or smoke when using this product. Clean equipment, work area and **General Hygiene Considerations**

clothing regularly. Handle in accordance with good industrial hygiene and safety practices.

PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance Light Brown Liquid Physical state Not available Odor

No information available **Odor Threshold**

Not applicable Not applicable Melting point / melting range

Boiling point / boiling range No information available

Flash Point > 200 °C / > 392 °F COC ASTM D92

Evaporation Rate No information available Flammability Limit in Air No information available **Explosion Limits** No information available

34070101-00000C010 - Subaru Synthetic Motor Oil SAE 0W-20 GF-6, Keep Full

Revision Date: 08-Feb-2021

Vapor pressure @20 °C (kPa)No information availableVapor densityNo information availableDensity0.84 g/cm³ @15°CSolubility(ies)No information availablePartition coefficientNo information availableAutoignition TemperatureNo information availableDecomposing TemperatureNo information available

Kinematic viscosity @40C = 44.09 cSt; @100C = 6.8 cSt

9.2. Other information

DMSO extract by IP346 Less than 3.0 wt% (mineral oil component only)

10. STABILITY AND REACTIVITY

10.1. Reactivity

Reactivity The product is chemically stable.

10.2. Chemical stability

Chemical Stability Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Possibility of Hazardous Reactions None under normal processing.

10.4. Conditions to avoid

Conditions to Avoid Heat, flames and sparks.

10.5. Incompatible materials

Incompatible Materials Strong oxidizing agents

10.6. Hazardous decomposition products

Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and

vapors.

11. TOXICOLOGICAL INFORMATION

11.1 Information on likely routes of exposure

Inhalation May cause irritation of respiratory tract.

Eye contact May cause slight irritation.

Skin Contact May cause skin irritation and/or dermatitis.

Ingestion May be harmful if swallowed.

11.2 Information on toxicological effects

Symptoms No information available

11.3 Delayed and immediate effects as well as chronic effects from short and long-term exposure

Not classified. Skin corrosion/irritation

Serious eye damage/eye

irritation

Not classified.

Sensitization Not classified.

Mutagenic effects Not classified.

Not classified Reproductive Toxicity

STOT - single exposure Not classified.

STOT - repeated exposure Not classified

Not classified. **Aspiration hazard**

11.4 Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as Carcinogenicity:

a known or anticipated carcinogen by NTP, IARC, OSHA or ACGIH.

NTP (National Toxicology Program), IARC (International Agency for Research on Cancer), Legend:

OSHA (Occupational Safety and Health Administration of the US Department of Labor),

Revision Date: 08-Feb-2021

ACGIH (American Conference of Governmental Industrial Hygienists)

11.5 Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

Product Information (Estimated):

>5,000 mg/kg ATEmix (oral) ATEmix (dermal) >5,000 mg/kg ATEmix (inhalation-dust/mist) >5 mg/l

12. ECOLOGICAL INFORMATION

12.1 Ecotoxicity

No known significant effects or critical hazards. Plants and animals may experience harmful **Ecotoxicity effects**

or fatal effects when coated with petroleum products. Petroleum-based (mineral) lubricating oils normally will float on water. In stagnant or slow-flowing waterways, an oil layer can cover a large surface area. As a result, this oil layer might limit or eliminate natural atmospheric oxygen transport into the water. With time, if not removed, oxygen depletion in

the waterway may be sufficient to cause a fish kill or create an anaerobic environment.

The hydrocarbons in this material are not readily biodegradable, 12.2 Persistence and degradability

but since they can be degraded by microorganisms, they are

regarded as inherently biodegradable.

12.3. Bioaccumulative potential No information available.

12.4 Mobility in Environmental Media No information available.

12.5 Other adverse effects: No information available.

PBT and vPvB assessment

No information available

13. DISPOSAL CONSIDERATIONS

Hazard characteristic and regulatory waste stream classification can change with product use. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition.

Waste Disposal Method This material, as supplied, is not a hazardous waste according to Federal regulations (40

CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local

Revision Date: 08-Feb-2021

regulations for additional requirements.

Contaminated packaging Dispose of in accordance with local regulations.

14.TRANSPORT INFORMATION

DOT Not regulated

DOT - Bulk Not regulated

<u>IATA</u> Not regulated

IMDG Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA	All ingredients are on the inventory or exempt from listing
DSL/NDSL	All ingredients are on the inventory or exempt from listing
ENCS	All ingredients are on the inventory or exempt from listing
IECSC	All ingredients are on the inventory or exempt from listing
KECL	All ingredients are on the inventory or exempt from listing
PICCS	All ingredients are on the inventory or exempt from listing
AICS	All ingredients are on the inventory or exempt from listing
NZIoC	All ingredients are on the inventory or exempt from listing

USA

Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazardous Categorization

Acute health hazard No
Chronic Health Hazard No
Fire hazard No

Revision Date: 08-Feb-2021

Sudden Release of Pressure Hazard No Reactive Hazard No

CERCLA/SARA 302 & 304

Section 302 & 304 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 355.

Chemical name	CAS-No	weight-%	RQ	TPQ
Toluene	108-88-3	<0.0001	RQ 1000lb final RQ RQ 454kg final RQ	
Ethyl benzene	100-41-4	<0.0001	RQ 1000lb final RQ RQ 454kg final RQ	
1,4-Dioxane	123-91-1	<0.0001	RQ 100lb final RQ RQ 45.4kg final RQ	
Benzene	71-43-2	<0.0001	RQ 10lb final RQ RQ 4.54kg final RQ	
Naphthalene	91-20-3	<0.0001	RQ 100lb final RQ RQ 45.4kg final RQ	
Ethylene Oxide	75-21-8	<0.0001	RQ 10lb final RQ RQ 4.54kg final RQ	1000 lb TPQ
Propylene oxide	75-56-9	<0.0001	RQ 100lb final RQ RQ 45.4kg final RQ	10000 lb TPQ

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

Chemical name	CAS-No	weight-%	HAPS data
Toluene	108-88-3	<0.0001	X
Ethyl benzene	100-41-4	<0.0001	X
1,4-Dioxane	123-91-1	<0.0001	X
Benzene	71-43-2	<0.0001	X
Naphthalene	91-20-3	<0.0001	X
Ethylene Oxide	75-21-8	<0.0001	X
Propylene oxide	75-56-9	<0.0001	X

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CAS-No	weight-%	U.S CWA (Clean Water Act)
Zinc dialkyl dithiophosphate	2215-35-2	<1	X
zinc bis[O,O-bis(2-ethylhexyl)] bis (dithiophosphate)	4259-15-8	<1	X
Toluene	108-88-3	<0.0001	X
Ethyl benzene	100-41-4	<0.0001	X
Benzene	71-43-2	<0.0001	X
Naphthalene	91-20-3	<0.0001	X
Propylene oxide	75-56-9	<0.0001	X

State Regulations

California Proposition 65

Label:

 \triangle

.WARNING Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Revision Date: 08-Feb-2021

Chemical name	CAS-No	weight-%	California Prop. 65	Maximum Allowable Dose for Reproductive Toxicity (MADLS)	Safe Harbor Limits for Cancer-causing Chemicals (NSRLs)
Toluene	108-88-3	<0.0001	Developmental	7000µg/daylevel represents absorbed dose	
Ethyl benzene	100-41-4	<0.0001	Carcinogen		54 μg/day inhalation 41 μg/day oral
1,4-Dioxane	123-91-1	<0.0001	Carcinogen		30 µg/day
Benzene	71-43-2	<0.0001	Carcinogen Developmental Male Reproductive	24µg/dayoral 49µg/dayinhalation	6.4 μg/day oral 13 μg/day inhalation
Naphthalene	91-20-3	<0.0001	Carcinogen		5.8 µg/day
Ethylene Oxide	75-21-8	<0.0001	Carcinogen Developmental Female Reproductive Male Reproductive	20µg/day	2 µg/day
Propylene oxide	75-56-9	<0.0001	Carcinogen		

State Right-to-Know

This product does not contain any substances regulated by state right-to-know regulations

16. OTHER INFORMATION

1 0 m

NFPA Health hazards: 1 Flammability: 1 Instability: 0

Prepared By: Aaron Keck

Revision Date: 08-Feb-2021

Revision Summary: Section 1: Identification of the hazardous chemical and of the supplier

Disclaimer:

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet